Scotsman UNDERCOUNTER UNITS

UF1415 - 140 lb Flake Ice Machine

Self-Contained Undercounter Ice Machine with Storage

Features and Benefits

Space Saving Design:

- Only 15" wide, this ice maker can be placed it the tightest locations
- Front breathing No side clearance required for flexible placement
- Optional floor mount kit allows for installation under 34" ADA counter tops

Ease of Use:

- Unit specific QR code for quick access to service manuals, cleaning guides and warranty history
- Ergonomic slide back door allows easy access to ice in the bin
- Power cord, NEMA 5-15P plug, ice scoop and adjustable legs are included for quick and easy installation

Reliability:

- Sealed, maintenance-free bearings for reduced preventative maintenance and long-lasting performance
- Stainless steel evaporator and auger for maximum durability
- Heavy duty, rust-free front panel and corrosion-resistant aluminum alloy side panels for maximum lifespan
- 3 Year parts and labor warranty
- Designed, engineered and assembled in the USA

High Production:

 Produces up to 142 lb (64 kg) per day and stores 36 lb (16 kg), maximizing ice output despite its small footprint

Environmentally Friendly:

- Energy Star certified
- Meets US Safe Drinking Act low lead requirements
- Non-ozone depleting R-134A refrigerant





Sealed, maintenance-free bearings ensure maximum reliability and contribute to a long machine life



Unit specific QR code for quick access to service manuals, cleaning guides and warranty history



Ergonomic slide back door allows easy access to ice in the bin



ADA compliant with optional floor mount kit












- 3 years parts and labor on all components
- Warranty valid in North, South & Central America for commercial installations
- Contact factory for warranty in other regions
- Residential Applications: 1 year parts and labor



- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN Fax: 847-913-9844 www.scotsman-ice.com customer.relations@scotsman-ice.com •










Front breathing and no side clearance required, allowing for flexible placement



Specifications

Energy Consumption Potable Water Usage Max. Fuse Size Storage Gallons/100 lb (liters/45.4 kg) **Basic Electrical** kWh/100 lb (45.4 kg) Model Condenser or HACR Circuit Min. Circuit Capacity Circuit 90°F(32°C)/70°F(21°C) Number Unit lb/kg Volts/Hz/Phase Breaker (amps) Wires Ampacity 90°F(32°C)/70°F(21°C) 12/45.5 UF1415A-1 36/16 115/60/1 Cord 5.29



All Models

Dimensions (W x D x H):

Unit: 15" X 24" X 38"

(38.1 x 61.0 x 96.5 cm)

Includes 6" (15.24 cm) adjustable legs

Shipping Carton: 22" x 27" x 38"

(55.9 x 68.6 x 96.5 cm)

Shipping Weight: 109 lb / 49 kg

BTUs per hour: 2,300

Refrigerant: R-134A



Model Number	Description	
KLP8S	Kit, Leg 6", Stainless Steel	
KBC1	Kit, Casters	
KUFM15	For ADA applications. Floor mount kit lowers overall height to 31.9"	

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

				,	
		Minimum	Maximum		
	Air Temperatures	50°F (10°C)	100°F (38°C)		
	Water Temperatures	40°F (4.4°C)	100°F (38°C)		
	Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)		
Ĺ	Electrical Voltage	-5%	+10%		

Specifications and design are subject to change without notice.

• 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •

• 1-800-SCOTSMAN • Fax: 847-913-9844 • www.scotsman-ice.com • customer.relations@scotsman-ice.com •

